Illinois, Indiana, Iowa, and SW Michigan
Phone: 800-953-7626 • 630-595-8400
Fax: 630-595-2386

Lesman Instrument Company
www.lesman.com
sales@lesman.com

Wisconsin, and Upper Peninsula Michigan
Phone: 800-837-1700 • 262-923-1790
Fax: 262-923-1797

LESMAN
Instrument Company
www.lesman.com

Chicagoland Office
Phone: 800-953-7626
Fax: 630-595-2386
E-mail: sales@lesman.com

Milwaukee Area Office
Phone: 800-837-1700
Fax: 262-923-1797

Contact: _____ Ext. _____

Name: _____
Company: _____
Street: _____
City: _____ State: _____ Zip: _____
Phone: (____) _____ Fax: (____) _____
E-mail Address: _____
This is a: ☐ Request for Quote ☐ Order: PO# _____
Quantity Needed: _____ Date Required: ____/____/____
Shipping Method: _____ Partials Accepted: ☐ Yes ☐ No

Fluidic Flowmeters

Oscillatory Flowmeters
Application Datasheet

Process Data

Flow Medium _____

Viscosity _____ CPS

Specific Gravity _____

Reference Temperature _____

Particle Size (if any) _____ Max.

Density _____ ☐ g/cm³ ☐ lb/ft³

Process Conditions	Min.	Normal	Max.	Units
Temperature	_____	_____	_____	☐ °C ☐ °F
Pressure	_____	_____	_____	☐ PSI ☐ bar

	Minimum	Normal	Full Scale	
Flow Rate Required	_____	_____	_____	GPM

Meter Body Specifications

Material ☐ 316SS ☐ Other _____

Pipe Size ☐ 0.75" ☐ 1" ☐ 1.5" ☐ 2" ☐ 3"

End Connections ☐ 150# Flange ☐ 300# Flange ☐ 600# Flange ☐ Wafer (Flangeless)

Deflection Sensor
☐ 316L SS with Standard Length Leads
☐ 316L SS with Long Leads for Junction Box
☐ 316L SS for Cryogenic Use
Must use signal converter.

Transmitter Specifications

Electronics Type
☐ Two-Wire Transmitter *(Not for Cryogenic Use)*
☐ Signal Converter

Service ☐ Analog ☐ Totalizing ☐ Batching

Output Required
☐ 4-20 mA
☐ 4-20 mA and Scaled or Unscaled Pulse

Approval Required
☐ None
☐ FM Intrinsically Safe Class I–III, Div 1, Grps A-G

Options

Please list any options or special requirements