

Chicago Area Office
135 Bernice Dr, Bensenville IL 60106
Ph: 800-953-7626 • 630-595-8400
Fax: 630-595-2386

Milwaukee Area Office
5160 N 125th St, Butler WI 53007
Ph: 800-837-1700 • 262-923-1790
Fax: 262-923-1797

E-mail: sales@lesman.com

Contact: _____ Ext. _____

Name: _____

Company: _____

Street: _____

City: _____ State: _____ Zip: _____

E-mail Address: _____

Phone: (____) _____ Fax: (____) _____


This is a: Request for Quote Order: PO# _____

Quantity Needed: _____ Date Required: ____/____/____

Shipping Method: _____ Partial Accepted: Yes No

Veris Accelabar

Application Datasheet



Process Conditions

Media Type: _____

	Min.	Normal	Max.	Units
Flow Rate:	_____	_____	_____	GPM

Process Pressure: _____ PSI bar

Process Temperature: _____ °C °F

Specific Gravity: _____

Molecular Weight (Gas): _____

Process Pipe

Pipe Size: _____ Pipe Schedule: _____

Pipe ID: _____ Wall Thickness: _____

Pipe Material: _____

Pipe Orientation: Horizontal Vertical

Special Instructions/Notes:

Flowmeter Selection

- ANSI Flanged: 150# 300#
 600# ABS Bevel for Weld
- Meter Size: 3" 4"
 6" 8"
 10" 12"


Instrument Head Connection: (Sold Separately)

Direct Mount Transmitter
(Flanged 450°F Max.)



Manifold Transmount

Remote Mount Transmitter
(1/2" NPT)



Valve Regular Parallel

Manifold: (optional)



3-Valve 5-Valve


Seat Type:

- Hard
 Soft

Material:

- Carbon Steel
 Stainless Steel

Instrument Valves: (optional)



Needle Gate

Material:

- Carbon Steel
 Stainless Steel

Optional Components

- RTD: Non-Hazardous Location
 Hazardous Location, Class 1 Div 1, Explosion Proof
 Hazardous Location, Class 1 Div 2, Non-Incendive Wiring
 High Temperature (500° to 900°F, 260° to 482°C)

Connection Cable to Transmitter: (Direct Mount Only)

- Explosion Proof (hazardous locations)
 NEMA 4

Transmitter

Supplied By: Veris Other