

NEW!

Easier. Faster. Affordable!

MFC5150x Intrinsically Safe, HART®-Compliant Communicator

Preloaded
with every
available
HART® DD!

- Free upgrades/downloads for life of the product - no subscriptions!
- Reads manufacturers' DDs in their native format — no translations needed
- HART®-compliant modem communicates with any HART® device
- Large 4.3" touchscreen (no stylus required)
- Full QWERTY keyboard for commissioning new transmitters
- On Demand Help Menus and teachable device-specific short cuts
- More than twice the battery capacity of any handheld communicator
- PC utility for easy transfer of configurations
- Ability to switch between 10 preloaded languages live
- Gesturing similar to that of a mobile phone

Charger included with
integrated USB connectivity

The MFC5150 is certified in the following Hazardous locations: • Class I, Division I Group IIC (US/Canada)
• ATEX Zone 0 Group IIC (Europe) • IECex Zone 0 Group IIC (Asia, South America, Africa)



Find out more at www.meriam.com

Or contact us at: 216.281.1100 | E-mail: sales@meriam.com



The MFC5150x utilizes a Windows™ based system for faster processing and greater storage capacity. Plus, no subscriptions, and with all options standard at no extra cost, it's more affordable than ever. It's the Power of a PC in the palm of your hand!

Display	Type	Transflective Display with anti-glare touch screen (Resistance film)	USB	Data rate Form	Supporting up to 921.6 kbps USB B type (receptacle)		
	Size	4.3-inch WQVGA	Intrinsic Safety	ANSI/ISA (US)	UL913 Ed7 UL60079-0 Ed5 UL60079-11 Ed5 CSA-C22.2 NO. 157-92(R2012) NO. 60079-0:11 NO. 60079-11:11 EN60070-0:2012 EN60079-11:2012 EN60079-26:2007	CL I, DIV 1, GP A,B,C,D; T4 CL I, ZONE 0, AEx ia IIC T4 CL I, DIV 1, GP A,B,C,D; T4 CL I, ZONE 0, Ex ia IIC T4	
	Color	24bit (16,777,216) TFT color		ANSI/ISA (Canada)			
	Pixel	480 X 272 pixels		ATEX (Europe)		II 1 G Ex ia IIC T4 Ga	
	Backlight	White LED		IECEX (International)	IEC60079-0:2011 Ed6 IEC60079-11:2011 Ed6 IEC60079-26:2006 Ed2	Ex ia IIC T4 Ga	
Body	Size	11.9×5.6×1.9 inch [303×142×48 mm]	FCC (US), CE (Europe)	FCC (US) CE (Europe) C-tick (Australia) ANSI-ISA	EN61326-1 EN61326-2-3		
	Weight	Approximately 2.1 lbs [0.95 Kg] with battery		Electrical Equipment Safety	UL (US) ANSI (US) CSA (Canada) CE (Europe)	UL61010-1 Ed3 UL60950-1 CSA-C22.2 NO. 61010-1-12 EN60950-1	AC Adapter AC Adapter
Keyboard	Material	Molded Keyboard design w/tactile feedback	Environmental Protection	RoHS WEEE REACH	Directive 2011/65/EU Directive 2002/96/EC Regulation (EC) No 1907/2006		
	Key	52 keys including qwerty keys	Transportation	IATA	UN/DOT 38.3	Li-ion Battery	
Power	Rechargeable Battery	Li-Ion	Field Communication	HART® Communication Host			
Battery Life	Continuous use	10 hours	Operating System	Manufacture Revision	Microsoft Windows™ CE		
	100% backlight	20 hours	Internal Memory	FlashROM RAM	NAND 512MByte DDR 256mb		
	Average use	40 hours	Supported HART® Communication revisions	HART5, 6, 7			
Rechargeable battery	Voltage output	3.7VDC	Languages supported	English, French, German, Italian, Japanese, Polish, Portuguese, Romanian, Russian, Spanish			
	Current capacity	2000mA	Applicable Equipment	All transmitters supporting HART® Communication protocol			
	Energy capacity	9480mAh	Included Accessories	Handy carry case material	Ballistic Nylon; inside material black 420 Nylon		
	Charging time	6 hours		HART® leads	Molded banana plug test leads 39.4 inch [1m] long		
Battery Charger (AC adapter)	AC adapter Form	Wall Adapter Four international inserts (US-U,UK-B,EU-E,AU-A)		Strap	Wrist strap		
	Input voltage	100-240VAC 50/60Hz		USB cable	78.7 inches [2m] Type A to USB Type B		
	Output voltage	15VDC		CD-ROM	Documentation, Drivers, PC Utility		
	Output current	1600mA					
	Overcharge protection	Yes					
	LED indication	N/A					
Battery Charger (Cradle)	LED indication	Yes, Tri color LED					
Normal operating Condition	Ambient temp.	+14°F (-10°C) to +122°F (+50°C)					
	Ambient humidity	0% to 95% RH (non-condensing) (for +32°F (0°C) to +122°F (+50°C))					
Storage condition	Ambient temp. with battery	-4°F (-20°C) to +131°F (+55°C)					
	Ambient temp. without battery	-4°F (-20°C) to +150°F (+60°C)					
	Ambient humidity with battery	0% to 95% RH (non-condensing) (for +32°F (0°C) to +122°F (+50°C))					
	Ambient humidity without battery	0% to 95% RH (non-condensing) (for +32°F (0°C) to +122°F (+50°C))					
Charging condition	Ambient temp.	+50°F (+10°C) to +104°F (+40°C)					
	Ambient humidity	0% to 95% RH (non-condensing)					
	Other	Only safety area when charging					
Enclosure Rating	Body	IP51					
Shock condition	Tested to survive a 39.4 inch [1m] drop onto concrete						
HART® connections	Form	Two banana plugs spaced ¾ inch					
Storage	Media type	microSD card					
	Capacity	4GB Minimum					



Find out more at www.meriam.com

Or contact us at: 216.281.1100 | E-mail: sales@meriam.com