


Name: _____
 Company: _____
 City: _____ State: _____
 When do you need a quote? _____
 When do you need the equipment on site? _____
 When will you place the order? _____

Veris Accelabar Application Datasheet



Process Conditions

Media Type: _____

	Min.	Normal	Max.	Units
Flow Rate:	_____	_____	_____	_____
Process Pressure:	_____	_____	_____	<input type="checkbox"/> PSI <input type="checkbox"/> bar
Process Temperature:	_____	_____	_____	<input type="checkbox"/> °C <input type="checkbox"/> °F

Specific Gravity: _____
 Molecular Weight (Gas): _____

Process Pipe

Pipe Size: _____ Pipe Schedule: _____
 Pipe ID: _____ Wall Thickness: _____
 Pipe Material: _____
 Pipe Orientation: Horizontal Vertical

Special Instructions/Notes:

Flowmeter Selection

ANSI Flanged: 150# 300#
 600# ABS Bevel for Weld

Meter Size: 3" 4"
 6" 8"
 10" 12"

Instrument Head Connection: (Sold Separately)

Direct Mount Transmitter
(Flanged 450°F Max.)



Manifold Transmount

Remote Mount Transmitter
(1/2" NPT)



Valve Regular Parallel

Manifold: (optional)



3-Valve 5-Valve

Seat Type:

Hard
 Soft

Material:

Carbon Steel
 Stainless Steel

Instrument Valves: (optional)



Needle Gate

Material:

Carbon Steel
 Stainless Steel

Optional Components

RTD: Non-Hazardous Location
 Hazardous Location, Class 1 Div 1, Explosion Proof
 Hazardous Location, Class 1 Div 2, Non-Incendive Wiring
 High Temperature (500° to 900°F, 260° to 482°C)

Connection Cable to Transmitter: (Direct Mount Only)

Explosion Proof (hazardous locations)
 NEMA 4

Transmitter

Supplied By: Veris Other