

**SITRANS General Clamp-On Flowmeter Application Data Sheet**  
**FS230 / FS220**

Email To: [piabusales.industry@siemens.com](mailto:piabusales.industry@siemens.com) or FAX TO: 972-522-4503

**Instructions:** Navigate through the form using the TAB key or mouse. To select a checkbox, click with mouse or press the SPACEBAR. To select units, click and choose from drop-down menu.

Requestor Information		Customer Information		End-User Information	
Company Name:	<input type="text"/>	Company Name:	<input type="text"/>	Company Name:	<input type="text"/>
Requestor Name:	<input type="text"/>	City:	<input type="text"/>	City:	<input type="text"/>
Phone:	<input type="text"/>	State*:	<input type="text"/>	State*:	<input type="text"/>
E-mail	<input type="text"/>	Country*:	<input type="text"/>	Country*:	<input type="text"/>

**Selected Part Numbers:**

7ME

**Process Information**

**Liquid Data:**

Liquid Name / Description:	<input type="text"/>	Solids or Gas:	<input type="text"/> % (If Applicable)	Particle Size:	<input type="text"/> (If Known)
Temp Range:	Min: <input type="text"/> Typ: <input type="text"/> Max: <input type="text"/>	<input type="checkbox"/> °F <input type="checkbox"/> °C			
Pressure @ zero flow:	<input type="text"/> <input type="checkbox"/> BAR <input type="checkbox"/> PSI	Pressure @ nominal flow:	<input type="text"/> <input type="checkbox"/> BAR <input type="checkbox"/> PSI		
Viscosity	<input type="text"/> @ Temp <input type="text"/> <input type="checkbox"/> °F <input type="checkbox"/> °C				
S.G. or API	<input type="text"/> @ Temp <input type="text"/> <input type="checkbox"/> °F <input type="checkbox"/> °C				

**Thermal Energy Data:** (for FUE1010 Energy flowmeter only)

Supply temperature:	Min: <input type="text"/> Typical: <input type="text"/> Max: <input type="text"/>	<input type="checkbox"/> °F <input type="checkbox"/> °C	Glycol Ratio (if present):	<input type="text"/> %	
Return temperature	Min: <input type="text"/> Typical: <input type="text"/> Max: <input type="text"/>	<input type="checkbox"/> °F <input type="checkbox"/> °C	Sensor Location :	<input type="checkbox"/> Supply	<input type="checkbox"/> Return

**Process:**

Flow Volume Units		Flow Time Units	
Flow Rate:	Min: <input type="text"/> Typ: <input type="text"/> Max: <input type="text"/>		
The Flow is:	<input type="checkbox"/> Continuous <input type="checkbox"/> On/Off <input type="checkbox"/> Pulsating <input type="checkbox"/> Single Direction <input type="checkbox"/> Bi-Directional		
If On/Off or Pulsing, describe on/off times or batch size:	Time on: <input type="text"/>	Time off: <input type="text"/>	Batch Size <input type="text"/>

**Installation**

**Pipe Data:**

Actual Outside Diameter:	<input type="text"/> <input type="checkbox"/> Inches <input type="checkbox"/> mm	<OR> Nominal Pipe Size:	<input type="text"/> <input type="checkbox"/> Inches <input type="checkbox"/> mm
Pipe Material:	Other: <input type="text"/>	Material Class:	Other: <input type="text"/>
Pipe Wall Thickness:	<input type="text"/>	Pipe Schedule:	<input type="text"/> Other: <input type="text"/>
Liner Material:	Other: <input type="text"/>	Liner Thickness:	<input type="text"/> <input type="checkbox"/> Inches <input type="checkbox"/> mm

### Flow Sensor Location:

Straight run in pipe diameters:	Up stream:	Down stream:
Length of unobstructed pipe:	<input type="text"/> <input type="checkbox"/> Feet <input type="checkbox"/> Meters	Both sides of pipe accessible? <input type="checkbox"/> Yes <input type="checkbox"/> No
Pipe Orientation	<input type="checkbox"/> Horizontal <input type="checkbox"/> Vertical <input type="checkbox"/> Inclined	Direction of flow for vertical / inclined <input type="checkbox"/> Up <input type="checkbox"/> Down
Full Pipe?	<input type="checkbox"/> Yes <input type="checkbox"/> Partial <input type="checkbox"/> Intermittent	

### Flow Sensor Data:

Type; Choose all applicable	<input type="checkbox"/> Submersible <input type="checkbox"/> Dedicated <input type="checkbox"/> Portable <input type="checkbox"/> High Temperature Other: <input type="text"/>
Sensor Mounting:	<input type="checkbox"/> Standard (Aluminum) frames / tracks <input type="checkbox"/> Stainless Steel enclosures
Will sensors be located:	<input type="checkbox"/> Indoors <input type="checkbox"/> Outdoors
Will sensors be installed in a hazardous area?	<input type="checkbox"/> Yes <input type="checkbox"/> No
If yes, Agency and Area Rating <input type="checkbox"/> FM/CSA	Protection type: Other: <input type="text"/>

### Temperate Sensor (RTD) Data: (for FEC920 Thermal Energy flowmeter only)

RTD Temperature Element:	<input type="checkbox"/> Clamp-On <input type="checkbox"/> Insert	If insert, desired stem length	<input type="text"/> <input type="checkbox"/> Inches <input type="checkbox"/> mm
RTD thermowell to be supplied by Siemens	<input type="checkbox"/> Yes <input type="checkbox"/> No	Thermo-well Construction	<input type="checkbox"/> Standard <input type="checkbox"/> Tapered
Pipe is insulated: <input type="checkbox"/> Yes <input type="checkbox"/> No	Insulation Type:	Insulation Thickness	<input type="checkbox"/> in <input type="checkbox"/> mm
For temperature sensors (with the FEC920) Select Ohm value 100Ω <input type="checkbox"/> 500Ω <input type="checkbox"/> 1000Ω <input type="checkbox"/> Wire number: 3 wire <input type="checkbox"/> 4 wire <input type="checkbox"/>			

### Cables:

Length from transducer to flowmeter:	<input type="text"/> <input type="checkbox"/> Feet <input type="checkbox"/> Meters	Type:	Other: <input type="text"/>
--------------------------------------	--	-------	-----------------------------

### **Transmitter**

Will flow transmitter be installed in a hazardous area?	<input type="checkbox"/> Yes <input type="checkbox"/> No	Input Power
If yes, Approvals: <input type="checkbox"/> Choose <input type="checkbox"/> Protection type: Choose Other: <input type="text"/>		
Temperature @ Flow Transmitter	Min: <input type="text"/> Typ: <input type="text"/> Max: <input type="text"/>	<input type="checkbox"/> °F <input type="checkbox"/> °C

### Communications Channel #1:

### Outputs required - Channel #'s: 2, 3 & 4

<input type="checkbox"/> HART 4-20mA - Non-approved (Active/Passive)	<input type="checkbox"/> Non-approved (Active/Passive)	4-20mA Qty: <input type="text"/> freq Qty: <input type="text"/> pulse Qty: <input type="text"/> relay
<input type="checkbox"/> HART 4-20mA – EX-approved (Active)	<input type="checkbox"/> EX-approved (Active)	4-20mA Qty: <input type="text"/> freq Qty: <input type="text"/> pulse Qty: <input type="text"/> relay
<input type="checkbox"/> HART 4-20mA – EX-approved (Passive )	<input type="checkbox"/> EX-approved (Passive )	4-20mA Qty: <input type="text"/> freq Qty: <input type="text"/> pulse Qty: <input type="text"/> relay
<input type="checkbox"/> Modbus RTU (RS485) EX-approved		

### **Calibration**

Accuracy Required :	+/- <input type="text"/> % of <input type="checkbox"/> Span <input type="checkbox"/> Flow
<input type="text"/>	<input type="text"/>

Add additional application requirements or information below. You may also insert a photo or a sketch of the application if available: Simply copy and paste into this table. Bitmaps should be no larger than 640 X 480

--

0 Pixels.