

Bourdon Tube Pressure Gauges Stainless Steel Series, Solid Front Case Type 232.30 - Dry Case Type 233.30 - Liquid-filled Case

WIKA Datasheet 23X.30

Applications

- With liquid-filled case for applications with high dynamic pressure pulsations (add restrictor) or vibration
- Suitable for corrosive environments and gaseous or liquid media that will not obstruct the pressure system
- Process industry: chemical/petrochemical, power stations, mining, on and offshore, environmental technology, mechanical engineering and plant construction

Product Features

- Solid-front stainless steel case
- Excellent load-cycle stability and shock resistance
- All stainless steel construction
- Positive pressure ranges to 20,000 psi (1600 bar)

Specifications

Design

ASME B40.100 & EN 837-1

Sizes

2½", 4" & 6" (63, 100 and 160 mm)

Accuracy class

2½": ± 2½% of span (ASME B40.100 Grade A)

4" & 6": ± 1.0% of span (ASME B40.100 Grade 1A)

Ranges

Vacuum / Compound to 200 psi (16 bar)

Pressure from 0/15 (1 bar) to 0/15,000 psi (1000 bar)
- 2½", 4"

Pressure from 0/10 (0.6 bar) to 0/20,000 psi (1600 bar) - 6"
or other equivalent units of pressure or vacuum

Working pressure

2½": Steady: ¾ full-scale value
 Fluctuating: ⅔ full-scale value
 Short time: full-scale value

4" & 6": Steady: full-scale value
 Fluctuating: 0.9x full-scale value
 Short time: 1.3x full-scale value

Operating temperature

Ambient: -40°F to +140°F (-40°C to +60°C) - dry

-4°F to +140°F (-20°C to +60°C) - glycerine-filled

-40°F to +140°F (-40°C to +60°C) - silicone-filled

Medium: +392°F (+200°C) maximum - dry

+212°F (+100°C) maximum - liquid-filled



Bourdon Tube Pressure Gauge Model 232.30, 4"

Temperature error

Additional error when temperature changes from reference temperature of 68°F (20°C) ±0.4% of span for every 18°F (10°K) rising or falling.

Weather protection

Weather tight (NEMA 4X / IP65)

Pressure connection

Material: 316L stainless steel

Lower mount (LM)

Lower back mount (LBM) - for 2½" & 4" size only

¼" NPT or ½" NPT limited to wrench flat area

Bourdon tube

Material: 316L stainless steel

< 1,500 psi (100 bar): C-shape

≥ 1,500 psi (100 bar): Helical

Movement

Stainless steel

Dial

White aluminum with black lettering; 2½" with stop pin

Pointer

Black aluminum, adjustable

Case

304 stainless steel with solid baffle wall and blowout back (safety case)

Window

Polycarbonate (2½") and Safety Glass (4" & 6") with Buna-N gasket

Bezel ring


Stainless steel, bayonet-type

Case fill

Glycerine 99.7% - Type 233.30

Optional extras

- Other pressure connections
- Restrictors for applications with high dynamic pressure pulsations
- Monel® wetted parts (Type 26X.30)
- Front flange, SS (LBM only)
- Mounting lugs for wall mounting*
- 316SS case material
- Silicone or Halocarbon oil case filling
- Red drag pointer or mark pointer
- Non-adjustable pointer
- Safety glass window
- Custom dial layout
- Integral alarm contacts or transmitters
- Other pressure scales available:
bar, kPa, MPa, kg/cm² and dual scales



Size		A	B	C ¹	E	G	H	J	L	M	N	S	T	W	Weight
2.5"	mm	63	48	42	17.5	63	18.5	4	3	85	75	2		14	0.44 lb. dry
	in	2.48	1.89	1.65	0.69	2.48	0.73	0.16	0.12	3.35	2.95	0.08	1/4"	0.55	0.57 lb. filled
4"	mm	101	86	57.5	24	93	30	4.8	3	132	116	2		22	1.43 lb. dry
	in	3.98	3.35	2.26	0.94	3.66	1.18	0.19	0.12	5.20	4.57	0.08	1/2"	0.87	2.38 lb. filled
6"	mm	161	116	58	24	-	-	5.8	3	196	178	2		22	2.86 lb. dry
	in	6.34	4.57	2.28	0.94	-	-	0.23	0.12	7.72	7.01	0.08	1/2"	0.87	5.15 lb. filled

¹ For 6" LM range 20,000 psi, C dimension changes to 75.5 mm / 2.97 in.

² Weight without optional accessories.

Note: For 2½" size, front flange is a 2-piece design. Hole panel cutout dimension for this option is 66.5 mm.

* Note: When mounting rear lugs, leave 15 mm between the back of the gauge and the mounting surface.

Recommended panel cutout is dimension D + 1 mm

Ordering information

Pressure gauge model / Nominal size / Scale range / Size of connection / Optional extras required
Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing.
Modifications may take place and materials specified may be replaced by others without prior notice.



WIKA Instrument Corporation

1000 Wiegand Boulevard
Lawrenceville, GA 30043
Tel (770) 513-8200 Toll-free 1-888-WIKA-USA
Fax (770) 338-5118
E-Mail info@wika.com
www.wika.com